

Request for Quotations

TENDER OPENING LINK FOR 22 OCTOBER 2025

Wednesday, October 22 · 11:00am – 1:00pm

Time zone: Africa/Maputo

Google Meet joining info

Video call link: <https://meet.google.com/scx-qecr-qrs>

[illegible]

		- Overhaul Gasket Mazda BT50 Diesel - Front Shock Mazda BT50 diesel T6	30 30	
8.	RFQ822-25	Supply and delivery of the following - Rear shock Mazda B18 - Front Shocks Mazda B18 - Manual Fuel Pump B18 - Distributor Mazda B18 - Spark plugs Mazda B18	30 60 20 12 600	
9.	RFQ823-25	Supply and delivery of the following - Clutch slave NP200 - Fan NP200 - Radiator NP200 - Overhaul Gasket NP200 - Head Gasket NP200 - Stabilizer bar link NP200 - Timing Belt	60 30 30 30 60 120 30	
10.	RFQ824-25	Supply and delivery of the following 24v H4 Bulbs 12v HI Bulbs 12v H4 Bulbs - Fan Belts Mazda BT50 Petrol 2.2i - Front Hubs Chev Utility	120 300 300 60 30	
11.	RFQ825-25	Supply and delivery of the following - Idler Arm Mazda B18 - Lower Ball Joint Mazda B18 - Brake Pads Mazda B18 - Clutch Slave Cylinder B18	30 30 60 20	Mazda B18
12.	RFQ826-25	PURCHASE IS PER LOT Supply and delivery of: - Light duty grinder - Masonry disc 2.5mm cable red 2.5mm cable black 2.5mm cable earth - Armored cable 4 core 4mm 4way DB - Well glass fitting - Glass sphere fitting - Lamp holder 1gang 2way switch 2gang 2way switch 19mm PVC conduit - Double socket outlet 15amp - Double socket outlet 16amp 19mm pvc couplings 19mm pvc nipples - round box - round box cover	1 2 1 roll 1 roll 1 roll 80m 1 1 1 2 1 1 5 1 1 50 50 10 10	

		20. 6 x 6 square box (flash) 21. 3 x 3 square box (flash) 22. 90 degrees pvc bend 19mm 23. 100watt flood light 24. 60amp single pole breaker 25. 20amp single pole breaker 26. 5amp single pole breaker 27. Veranda bolts and nuts 12mm 28. Chasing hammer 29. Chasing comps 30. Spring bender 19mm 31. Fisher tape 32. 19mm saddles 33. Woodscrews 35 x 4mm 34. Self-tapping screws 35. Clout nails 2 inch 36. Cable gland and shroud size 0 37. 4mm crimping lugs 38. Copper earth rod 39. 10mm earth wire	4 2 10 3 1 1 1 10 1 6 1 1 20 50 25 25 3 10 1 15m	
13	827-25	For supply and delivery of the following T.Vs 1. Samsung Neomonitor 2. 75 inch smart TV As per attached specifications For urgent deliveries	1 2	Specifications attached below the table
14	828-25	For supply and delivery of the following items 1. Backdrop stand and Lighting Tripods 2. LED solar outdoor lighting As per attached specification For urgent deliveries	1set 8	Specification attached below the table
15	829-25	For supply and delivery kitchen utensils 1. 355 ltr Single door refrigerator 2. 45L microwave Defy/russel hobs/ As per attached specification For urgent deliveries	1 1	Specification attached below the table
16	830-25	For supply and delivery of the following items 1. 4K Resolution Digital Cameras & Lenses 2. 4K camera Drones As per attached specification For urgent deliveries	2 2	Specification attached below the table
17	832-25	Supply and delivery of 2025 Annual Stock Take Blue Stickers	10,000	See sample in Procurement
18	833-25	Supply and delivery of Cellphones • Samsung S24 512G Black Dual Sim • Iphone 16 Pus 256G Black/Purple DualSim • Samsung S24 ULTRA 256gb • Iphone 17 Pro 512gb Deep Blue	1 1 1 1	
19	834-25	Supply and delivery of HP Page Wide P5 7750 DW Waste Tonner	2	
20	835-25	Supply and delivery of 560W Panels	10	See attached

		Anti-theft Clips Charge Controller	40 1	Specification
--	--	---------------------------------------	---------	---------------

Closing date for ALL Tenders: On or before 11:00hrs; Wednesday 22 October 2025

Bidding Terms

- Quotations should be in US\$
- Payment Terms – 30 days
- Bidders to provide valid tax clearance certificate
- Bidders with outstanding orders for any of the above items will not be considered.
- TELONE RESERVES THE RIGHT TO INCREASE AND DECREASE QUANTITY
- Bidders should also be compliant with the new regulations for FISCAL TAX INVOICE where necessary.
- Each tender should be in its own envelope; tenders should not be mixed on one quotation.
- It is the Bidder’s responsibility to ensure that they receive a receipt confirming submission of their bid that has correct details of the Bidder and the number of the Bid.

Your Tender should state the price (Please state your VAT status), a firm delivery date Emailed to both procurement@telone.co.zw and procurement@telmail.co.zw. Physical copies to be **HAND DELIVERED** to TelOne, Procurement, 8th Floor, Runhare House.

RFQ 829-25

Microwave Specifications

Required is a 45L microwave oven

ITEM	SPECIFICATIONS		COMPLIANCE
1	Capacity	45 litres	
2	Type	Convection	
3	Power Output	1000W	
4	Exterior Dimensions	55 cm x 40 cm x 35 cm	
5	Interior Dimensions	40 cm x 30 cm x 25 cm	
6	Control Type	Digital	
7	Display	LED	
8	Cooking Modes	Auto Cook Menu	
9	Turntable	Yes (removable)	
10	Safety Features	Child lock	
11	Timer	Up to 99 minutes	
12	Interior Material	Stainless steel	
13	Energy Consumption	1000W	

** Indicate crucial feature for the microwave

Outdoor solar lights Specifications RFQ 828-25

Required is an outdoor solar light

ITEM		SPECIFICATIONS	COMPLIANCE
1	Type	Solar LED Outdoor Light	
2	Power Source	Integrated solar panel	
3	Battery Type	Lithium-ion	
4	Battery Capacity	4000mAh	
5	Brightness	1000 lumens	
6	Color Temperature	5000K (cool white)	
7	Light Modes	Motion sensor	
8	Panel Type	Monocrystalline	
9	Panel Wattage	10W	
10	Water Resistance Rating	IP65	
11	Material	ABS plastic	
12	Temperature Range	20°C to 60°C	
13	Mounting Type	Wall-mounted	
14	Sensor Range	10 meters	
15	Lifespan	30,000 hours for LED bulbs	
16	Warranty	2 years	

** Indicate crucial feature for the solar lights.

Studio Lighting kit Specification RFQ 828-25

Required is a studio lighting kit

ITEM		SPECIFICATIONS	COMPLIANCE
Backdrop			
1	Size	Medium (2m × 3m / 6.5ft × 10ft)	
2	Material	Polyester Fabric	
3	Color/Design	White	
4	Mounting System	Backdrop Stand Kit (Adjustable Aluminum Frame)	
5	Lighting Compatibility	Matte Finish Surface	
6	Accessories	Set of 6 Spring Clamps + Sandbags + Carry Bag	
7	Height Range	0.9 m to 3.0 m	
8	Width Range (Crossbar)	1.5 m to 3.6 m	
9	Pole / Tube Diameter	~ 30–50 mm outer diameter; wall thickness ~1.5–2.5 mm	
10	Load Capacity	10–30 kg	
11	Base / Feet / Support	Wide tripod legs or flat base plates;	
12	Locking Mechanism	Twist/knob locks, spring pins, or locking collars	
13	Weight (Stand Only)	3-8 kg	
15	Material / Finish	Aluminum alloy (often anodized or powder coated)	
16	Accessories	Spring clamps, sandbags / weight bags, carry bag / case, extension arms	
17	Rubber or Non-Slip Feet	Yes	
18	Optional Depth / Rear Leg Adjustment	20-60 cm	
Lighting Tripod			
19	Height Range	0.8 m to 2.5 m	
20	Minimum/Folded	40–50 cm	

	Height	
21	Load Capacity	5-10 kg
22	Leg / Tube Diameter	Leg tubes ~20-30 mm; central column/tubes ~22-30 mm
23	Material	Aluminum alloy
24	Locking Mechanisms	Knobs or twist locks for the tube sections; locking for leg spread angle

4K camera drones Specifications RFQ 830-25

Required is a 4K camera drone.

ITEM		SPECIFICATIONS	COMPLIANCE
		Aircraft	
1	Takeoff Weight	724 g	
2	Dimensions	Folded (without propellers): 214.19×100.63×89.17 mm (L×W×H) Unfolded (without propellers): 266.11×325.47×106.00 mm (L×W×H)	
3	Max Ascent Speed	10 m/s	
4	Max Descent Speed	10 m/s	
5	Max Horizontal Speed	At sea level, in windless conditions: 21 m/s* At sea level, with 6 m/s tailwind, while flying in the same direction as the wind: 27 m/s*	
6	Max Takeoff Altitude	6000 m	
7	Max Flight Time	45 minutes	
8	Max Hovering Time	41 minutes	
9**	Max Flight Distance	32 km	
10	Max Wind Speed Resistance	12 m/s	
11	Max Pitch Angle	36°	
12	Operating Temperature	-10° to 40° C (14° to 104° F)	
13	Global Navigation Satellite System	GPS + Galileo + BeiDou	
14	Hovering Accuracy Range	Vertical: ±0.1 m (with vision positioning) ±0.5 m (with satellite positioning) Horizontal: ±0.3 m (with vision positioning) ±0.5 m (with satellite positioning)	
15	Internal Storage	42 GB	
		Camera	
16	Class	C1 (EU)	
17	Wireless	Wi-Fi 4 (802.11 a/b/g/n/ac), Bluetooth 5.2	
18	Image Sensor	Wide-Angle Camera: 1-inch CMOS, 50MP Effective Pixels Medium Tele Camera: 1/1.3-inch CMOS, 48MP Effective Pixels	
19	Battery	Li-ion 4S,4276 mAh	
20	Lens	Wide-Angle Camera FOV: 84° Format Equivalent: 24 mm	

		Aperture: f/1.8 Focus: 0.5 m to ∞
		Medium Tele Camera FOV: 35° Format Equivalent: 70 mm Aperture: f/2.8 Focus: 3 m to ∞
21	ISO Range	Video Normal: 100-12800 (Normal) 100-3200 (D-Log M) 100-3200 (HLG) Slow Motion: 100-6400 (Normal) 100-3200 (D-Log M) 100-3200 (HLG) Photo 100-6400 (12 MP) 100-3200 (48 MP and 50 MP)
22	Shutter Speed	Wide-Angle Camera 12MP Photo: 1/8000-2 s (2.5-8 s for simulated long exposure) 50MP Photo: 1/8000-2 s Medium Tele Camera 12MP Photo: 1/16000-2 s (2.5-8 s for simulated long exposure) 48MP Photo: 1/8000-2 s
23	Max Image Size	Wide-Angle Camera: 8192×6144 Medium Tele Camera: 8064×6048
24	Photo Format	JPEG/DNG (RAW)
25	Video Resolution	Wide-Angle Camera/Medium Tele Camera: H.264/H.265 4K: 3840×2160@24/25/30/48/50/60/120*fps FHD: 1920×1080@24/25/30/48/50/60/120*/240*fps 2.7K Vertical Shooting: 1512×2688@24/25/30/48/50/60fps
26	Video Format	MP4 (MPEG-4 AVC/H.264, HEVC/H.265)
27	Color Mode and Sampling	Wide-Angle/Medium Tele Camera Normal (FHD/2.7K): 8-bit 4:2:0 (H.264) Normal (FHD/2.7K): 10-bit 4:2:0 (H.265) HLG/D-Log M (FHD/2.7K): 10-bit 4:2:0 (H.264/H.265) Normal/HLG/D-Log M (4K): 10-bit 4:2:0 (H.265)
28	Digital Zoom	Wide-Angle Camera: 1-2.9x Medium Tele Camera: 3-9x
		Gimbal
29	Stabilization	3-axis mechanical gimbal (tilt, roll, pan)
30	Mechanical Range	Tilt: -135° to 70° Roll: -50° to 50° Pan: -27° to 27°
31	Controllable Range	Tilt: -90° to 60° Pan: -5° to 5°
32	Max Control Speed (tilt)	100°/s
33	Angular Vibration Range	±0.0037°
34		DJI RC-N3 Remote Controller
35	Max Operating Time	Without Charging Any Mobile Device: 3.5 hours When Charging a Mobile Device: 1.5 hours
36	Max Supported Mobile Device Size	180×86×10 mm (L×W×H)
37	Charging Time	2 hours
38	Battery Capacity	9.36 Wh (3.6 V, 2600 mAh)
39	Weight	Approx. 320 g
41	Video Transmission Operating Frequency	2.4000-2.4835 GHz 5.170-5.250 GHz 5.725-5.850 GHz
40	Dimensions	104.2×150×45.2 mm (L×W×H)

** Indicate crucial feature for the camera and lens

Camera and Lens SpecificationsRFQ 830-25

Required is a 33-megapixel, full-frame mirrorless camera with a 3-inch vari-angle touchscreen, up to 10 fps shooting, and 5-axis image stabilization

ITEM	SPECIFICATIONS		COMPLIANCE
1	Lens Mount	Sony E	Actual: 34.1 Megapixel
2	Sensor Resolution	Actual: 34.1 Megapixel Effective: 33 Megapixel (7008 x 4672)	
3	Image Sensor	35.9 x 23.9 mm (Full-Frame)	CMOS
4	Image Stabilization	Sensor-Shift	
5	ISO/Gain Sensitivity	Photo Native in Manual Mode: 100 to 51,200 (50 to 204,800 Extended) Native in Auto Mode: 100 to 12,800 Video Native in Manual Mode: 100 to 51,200 (100 to 102,400 Extended) Native in Auto Mode: 100 to 51,200	
6	Internal Recording	H.264/XAVC S-I 4:2:2 10-Bit UHD 4K (3840 x 2160) at 24.00/30.00/60.00 fps [240 to 600 Mb/s] 1920 x 1080p at 23.98/25/29.97/50/59.94 fps [89 to 222 Mb/s]	
7	Hot-swap HDD bays	Yes	
8	NVMe Drives	2x Micron 7500 MAX 6400GB NVMe U.3 (15mm) 2.5" SSD Drive - PCIe Gen4	
9**	Nvidia Tesla and AMD FirePro GPU Compute Cards	4x NVIDIA RTX A6000 - 10752 Cuda Cores, 48GB ECC GDDR6	
10	PCI Express Expansion	Broadcom NetXtreme 10 Gigabit Ethernet Network Adapter P210P - PCIe 3.0 x8 - 2x 10GbE SFP+, Broadcom NetXtreme Gigabit Ethernet Network Adapter BCM5719-4P - PCIe 2.0 x16 - 4x RJ45,	
11	Video Output	4:2:0 8-Bit via HDMI UHD 4K (3840 x 2160) at 23.98/25/29.97/50/59.94 fps 1920 x 1080p at 23.98/50/59.94 fps 1920 x 1080i at 50/59.94 fps 4:2:2 10-Bit via HDMI UHD 4K (3840 x 2160) at 23.98/25/29.97/50/59.94 fps 1920 x 1080p at 23.98/50/59.94 fps 1920 x 1080i at 50/59.94 fps	
12	Media/Memory Card Slot	Slot 1: CFexpress Type A / SDXC (UHS-II) Slot 2: SD/SDHC/SDXC (UHS-II)	
13	Video I/O	1x HDMI Output	
14	Audio I/O	1x 1/8" / 3.5 mm TRS Stereo Headphone Output 1x 1/8" / 3.5 mm TRS Stereo Microphone Input	
15	Power I/O	1x USB-C Input	
16	Other I/O	1x Sony Multi/Micro-USB Remote Input 1x USB-C (USB 3.2 / 3.1 Gen 1) Data Input/Output (Shared with Power Input)	
17	Wireless	Wi-Fi 4 (802.11n), Bluetooth 4.1	
18	Display Type	Free-Angle Tilting 3" Touchscreen LCD	
19	Battery	1x NP-FZ100 Rechargeable Lithium-Ion, 7.2 VDC, 2280 mAh (Included) • Approx. 520 Shots	

** Indicate crucial feature for the camera and lens

Fridge Specifications

Required is a 355L single fridge with dimensions around 70 cm (depth) x 60 cm (width) x 175 cm (height), a weight of 63-66 kg, and features like no-frost technology, LED lighting, and adjustable shelves.

ITEM	SPECIFICATIONS		COMPLIANCE
1	Capacity	355 L	
2	Model	Single Door Refrigerator	
3	Gross Volume Total (L)	387 L	
4	Net Volume Total (L)	355 L	
5	Memory	8x 64GB 3200MHz DDR4 ECC Registered DIMM Module expandable to 4Tb	
6	Defrost System	No Frost	
7	Air Flow System	Multi & DynaCool	
8	Refrigerant	R600a	
9**	Compressor Type	Inverter	
10	Energy Consumption	185 kWh/year	
17	Warranty	1 year	

** Indicate crucial feature for the fridge

AI Server Specifications RFQ 827-25

Required is a Samsung Neo monitor.

ITEM	SPECIFICATIONS		COMPLIANCE
1	Screen Size (Class)	1m 45cm (57")	
2	Flat / Curved	Curved	
3	Active Display Size (HxV) (mm)	1394.6112 x 392.2344 mm	
4	Screen Curvature	1000R	
5	Aspect Ratio	32:9	
6	Panel Type	VA	
7	HDR (High Dynamic Range)	VESA DisplayHDR 1000	
8	Resolution	7,680 x 2,160	
9**	Viewing Angle (H/V)	178°(H)/178°(V)	
10	Refresh Rate	Max 240Hz	
11	Interface	HDMI 3 EA, Headphone, USB hub, Display Port	
12	Speaker Output	NO	
13	Stand Type	HAS	
14	Power supply	AC100-240V 50/60Hz	
15	Power Consumption (Max)	300 W	
16	Set Dimension with Stand (WxHxD)	1327.5 x 601.0 x 499.6 mm	

17	Set Weight with Stand	19.0 kg
18	Power Cable Length	1.5 m
19	HDMI Cable	Yes
20	Waranty	1 year

** Indicate crucial feature for monitor

AI Server Specifications RFQ 830-25

Required is a 75 inch smart TV.

ITEM		SPECIFICATIONS	COMPLIANCE
1	Screen diagonal size (inch)	75 in	
2	Screen diagonal size (cm)	190 cm	
3	Type	UHD Smart TV	
4	Resolution max	4K Ultra HD 3840x2160	
5	DTS Virtual X		
6	Series	A6BG	
7	Warranty	1 year	
8	Max. Resolution	4K Ultra HD	
9	Technology	QLED	

** Indicate crucial feature for the TV

RFQ 835-25

Charge Controller Technical Specifications

1.	Programmable charge voltage range	36 V-60 V
2.	Maximum charging current	120A
3.	Maximum DC PV voltage	600V DC
4.	Maximum DC PV voltage	450 V
5.	Start-up voltage	120 V
6.	MPPT operating voltage range	65 – 450 V
7.	Maximum PV array size per tracker (3)	7200 Wp
8.	Number of MPP Trackers	2

Solar PV Modules Technical Specifications

- Cell Type: Mono-crystalline solar pv modules
- Weight: in the range of 25-35 kg per module

- Front Cover: 3.2mm tempered glass with anti-reflective coating.
- Frame: Anodized aluminium alloy.
- J-Box: IP68 rated with bypass diodes for protection and performance optimization.
- Cable: 4 mm² (IEC) with optimized cable length complete with MC4 connectors.
- Power Output: The minimum wattage of 560Wp at Standard Testing Conditions
- Efficiency: > 23%
- Modules shall have a data plate showing Temperature Coefficients including: Temperature coefficients for power (P_{max}), open-circuit voltage (V_{oc}), and short-circuit current (I_{sc})
- Mounting: Standard mounting holes and grounding points